

Surface Mount Fuse, 3.2 x 1.6 mm, Super-Quick-Acting FF, 63 VDC / 125 VAC, low impedance



Exemplary part photo depending on part no.

UL 248-14 · 125 VAC · 63 VDC · Super-Quick-Acting FF



### Description

- Complements USF 1206 with lower current ratings
- Impermeable to potting compound

### Unique Selling Proposition

- Lowest voltage drop
- Very fast, precise opening

### Standards

- UL 248-14
- CSA C22.2 no. 248.14

### Approvals

- UL File Number: E41599

### Applications

- Smart meters
- Battery protection
- Sensors
- Mobile devices
- Semiconductor protection

### References

[Packaging Details](#)

### Weblinks

[pdf datasheet](#), [html-datasheet](#), [General Product Information](#), [Packaging details](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

### Technical Data

Rated Voltage	125 VAC, 63 VDC
Rated current	0.05 - 0.25 A
Breaking Capacity	100 A
Characteristic	Super-Quick-Acting FF
Mounting	PCB, SMT
Admissible Ambient Air Temp.	-55 °C to 90 °C
Climatic Category	55/090/21 acc. to IEC 60068-1
Material: Housing	Epoxyd Glass, UL 94V-0
Material: Terminals	Gold-Plated Copper Alloy
Unit Weight	0.0133 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	Letter (see variants)



Soldering Methods	Reflow <a href="#">Soldering Profile</a>
Solderability	245 °C / 3 sec acc. to IEC 60068-2-58, Test Td
Resistance to Soldering Heat	260 +0/-5 °C / 30 sec acc. to IPC/JEDEC J-STD-020D, Level 1
Moisture Resistance Test	MIL-STD-202C, Method 103 B (Level 1) IPC/JEDEC-J-STD-20C (85°C@85%RH@240h)
Terminal Strength	MIL-STD-202, Method 211A (Deflection of board 1 mm for 1 minute)
Thermal Shock	IEC 60068-2-14, CECC 4200 (5 Cycles 40°C - 125°C)
Case Resistance	acc. to EIA/IS-722, Test 4.7 >100 MΩ (between leads and body)
Resistance to Solvents	MIL-STD-202, Method 215A (EIA-722, 4.11)

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)


## Dimension

3.2 mm

Reflow soldering pads



## Derating Curves





## Pre-Arcing Time


Rated Current  $I_n$     1.0 x  $I_n$  min.    2.5 x  $I_n$  max.    10.0 x  $I_n$  min.    10.0 x  $I_n$  max.

Rated Current $I_n$	1.0 x $I_n$ min.	2.5 x $I_n$ max.	10.0 x $I_n$ min.	10.0 x $I_n$ max.
0.05 A	4 h	5 s	0.1 ms	1 ms
0.125 A	4 h	5 s	0.1 ms	3 ms
0.16 A - 0.25 A	4 h	5 s	0.1 ms	1 ms

Time-Current-Curves



All Variants

Rated Current [A]	Rated Voltage [VAC]	Rated Voltage [VDC]	Marking	Breaking Capacity	Voltage Drop 1.0 In typ. [mV]	Cold Resistance typ. [mΩ]	Melting I <sup>2</sup> t 8.0 In typ. [A <sup>2</sup> s]		Order Number
0.05	125	63	e	1)	430	8350	0.0002	●	3413.0002.11
0.05	125	63	e	1)	430	8350	0.0002	●	3413.0002.22
0.05	125	63	e	1)	430	8350	0.0002	●	3413.0002.24
0.05	125	63	e	1)	430	8350	0.0002	●	3413.0002.26
0.125	125	63	o	1)	260	2000	0.003	●	3413.0006.11
0.125	125	63	o	1)	260	2000	0.003	●	3413.0006.22
0.125	125	63	o	1)	260	2000	0.003	●	3413.0006.24
0.125	125	63	o	1)	260	2000	0.003	●	3413.0006.26
0.16	125	63	s	1)	95	510	0.0015	●	3413.0008.11
0.16	125	63	s	1)	95	510	0.0015	●	3413.0008.22
0.16	125	63	s	1)	95	510	0.0015	●	3413.0008.24
0.16	125	63	s	1)	95	510	0.0015	●	3413.0008.26
0.2	125	63	u	1)	87	365	0.0029	●	3413.0009.11
0.2	125	63	u	1)	87	365	0.0029	●	3413.0009.22
0.2	125	63	u	1)	87	365	0.0029	●	3413.0009.24
0.2	125	63	u	1)	87	365	0.0029	●	3413.0009.26
0.25	125	63	w	1)	75	255	0.0032	●	3413.0010.11
0.25	125	63	w	1)	75	255	0.0032	●	3413.0010.22
0.25	125	63	w	1)	75	255	0.0032	●	3413.0010.24
0.25	125	63	w	1)	75	255	0.0032	●	3413.0010.26

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

1) 10 A @ 125 VAC, 100 A @ 32 VAC, 100 A @ 63 VDC

Packaging Unit

- .xx = .11 Blister Tape of 100 pcs. in Plastic Bag
- .xx = .22 Blister Tape 18 cm Reel (1000 pcs.)
- .xx = .24 Blister Tape 25.4 cm Reel (5000 pcs.)
- .xx = .26 Blister Tape 33 cm Reel (10000 pcs.)

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.